

## HUBER Solutions for Filtration of Biologically Treated Wastewater



Filtration of biologically treated wastewater serves for removal of suspended solids (*suspensa*) remaining in clarifier effluents. Such *suspensa* contain about 50 % carbon, almost 10 % nitrogen and over 1 % phosphorus.

Around 1 mg/L (ppm) of phosphorus remain in the effluent, even if the biological treatment stage is designed for enhanced biological phosphorus removal and/or chemical phosphorus precipitation. Subsequent filtration is necessary where stringent phosphorus limits must be reliably maintained.

- Our rotary mesh screen **HUBER Disc Filter RoDisc®** is provided with fabric of a mesh size between 0.01 and 0.1 mm. The fabric is applied on both sides of slowly rotating discs.
- Wastewater flows continuously upstream through our **HUBER Sandfilter CONTIFLOW®**, and its sand bed is continuously backwashed.
- Membrane Bio-Reactors perform biological treatment and filtration. Our Membrane Filters retain not only all solids but also all bacteria within the bio-reactor.

---

**HUBER Technology de México, S. de R.L. de C.V.**  
Homero #136, Int. 1004, Col. Chapultepec Morales, México, D.F. C.P.11570  
Tel. (55) 5250 8886 & 6798 7339 \* [www.huber.mx](http://www.huber.mx)  
Empresa filial de HUBER SE, certificada ISO-9001 & ISO-14001, [www.huber.de](http://www.huber.de)